

8-19 Foot Tarp Kit 900W/90:1 Gear Motor - 4 Springs Without Wind Deflector

Buyers Part Number: 5546396

Buyers Products Underbody-Spring Mount Tarp System contains and protects your payload.

- Reliably covers and protects your payload.
- Slim underbody mount keeps the pivoting unit protected and out of the way.
- Choose from high speed, high torque or regular gear motors with 1 or 3 year warranties.
- Fingertip electric controls for ease of operation.
- Sturdy weather and corrosion-resistant aluminum components for reliable performance, time after time.
- Fits dump bodies from 8 ft to 23 ft long.

Specifications

| Arm Material | Aluminum | Arm Type | Telescoping |
|----------------------------------|-----------------------|------------------------------------|-------------|
| Circuit Breaker Amperage | 60 A | Dump Length Maximum | 19' |
| Dump Length Minimum | 8' | Motor Amperage | 75 A |
| Motor Gear Ratio | 90:1 | Motor Horsepower | 1.2 HP |
| Motor Mounting Pattern | 5 Hole | Motor Output Shaft Diameter | 0.75" |
| Motor Output Shaft Length | 3.13" | Motor Voltage | 12 VDC |
| Motor Wattage | 900 W | Number of Bumpers Included | 6 |
| Number of Springs per Arm | 1 | Solenoid Amperage | 150 A |
| System Style | Electric Underbody | Tarp Included (y/n) | No |
| Wind Deflector Included (y/n) | No | Wire Gauge | 8 Ga |
| Wire Length | 60' | Shipping Weight | 130.005 lb |