

14-23 Foot Tarp Kit 900W/60:1 Gear Motor - 5 Springs Without Wind Deflector

Buyers Part Number: 5547366

Buyers Products Underbody-Spring Mount Tarp System contains and protects your payload.

- Reliably covers and protects your payload.
- Slim underbody mount keeps the pivoting unit protected and out of the way.
- Choose from high speed, high torque or regular gear motors with 1 or 3 year warranties.
- Fingertip electric controls for ease of operation.
- Sturdy weather and corrosion-resistant aluminum components for reliable performance, time after time.
- Fits dump bodies from 8 ft to 23 ft long.

Specifications

Arm Material	Aluminum	Arm Type	Telescoping
Circuit Breaker Amperage	60 A	Dump Length Maximum	23'
Dump Length Minimum	14'	Motor Amperage	75 A
Motor Gear Ratio	60:1	Motor Horsepower	1.2 HP
Motor Mounting Pattern	5 Hole	Motor Output Shaft Diameter	0.75"
Motor Output Shaft Length	3.13"	Motor Voltage	12 VDC
Motor Wattage	900 W	Number of Bumpers Included	6
Number of Springs per Arm	1	Solenoid Amperage	150 A
System Style	Electric Underbody	Tarp Included (y/n)	No
Wind Deflector Included (y/n)	No	Wire Gauge	8 Ga
Wire Length	60'	Shipping Weight	130.005 lb