



<https://4jhoseandsupply.com>
 800-579-2315
 43 Highway 421 S.
 Bedford, KY 4006

RTW HOSE

Premium product: specially formulated thermoplastic provides a rubber-like look and feel at a fraction of the cost.

POTENTIAL USE:

- Heavy-duty Commercial & Construction Use
- General Water Service in Industrial Plants
- Municipal Maintenance and Park Departments
- Irrigation Supply Lines
- Heavy-duty Washdown
- Farm / Ranch Maintenance

FEATURES:

- RMA Class B Oil Resistance
- *Rubberized* Thermoplastic for enhanced flexibility
- Exceptional Abrasion Resistant Cover
- Excellent Resistance to Weather & Aging
- Available in Assembly or Bulk Form
- Heavy-duty Fittings on Each Assembly
- Outstanding value



CONSTRUCTION:

- **Tube:** Specially Formulated PVC
- **Reinforcement:** High Tensile Strength Textile Cord
- **Cover:** Specially Formulated PVC

TEMPERATURE: +15° F (1.7° C) to +150° F (+65° C)

BRANDING: Flex-Tech RTW Industrial Grade Water Hose - 5/8" I.D.

Part#	I.D.	O.D.	Max W.P.	Wt./ ft	Length	Type
ARTW0625XX100MF	5/8"	0.89	175 psi	0.185	100 ft	Assembly
ARTW0625XX75MF	5/8"	0.89	175 psi	0.185	75 ft	Assembly
ARTW0625XX50MF	5/8"	0.89	175 psi	0.185	50 ft	Assembly
ARTW0625XX25MF	5/8"	0.89	175 psi	0.185	25 ft	Assembly
RTW-0625XX-RL	5/8"	0.89	175 psi	0.185	500 ft	Reel
ARTW0750XX100MF	3/4"	1.06	175 psi	0.27	100 ft	Assembly
ARTW0750XX75MF	3/4"	1.06	175 psi	0.27	75 ft	Assembly
ARTW0750XX50MF	3/4"	1.06	175 psi	0.27	50 ft	Assembly
ARTW0750XX25MF	3/4"	1.06	175 psi	0.27	25 ft	Assembly
RTW-0750XX-RL	3/4"	1.06	175 psi	0.27	600 ft	Reel

*Working pressure decreased as temperature increases

*Weight/foot does not include fittings at each end

*For color replace **XX** with RD = red, GR = green, BK = black, BL = blue

*Custom length available upon request. Minimum orders will apply.